

## ANIOR ON UNDER CONTINUE CONTIN

TO ALL TO WHOM THESE: PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office

January 22, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

**APPLICATION NUMBER: 10/387,242** 

FILING DATE: March 12, 2003

**RELATED PCT APPLICATION NUMBER: PCT/US03/35337** 

By Authority of the COMMISSIONER OF PATENTS AND TRADEMARKS

H. L. JACKSON
Certifying Officer

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

**UTILITY PATENT APPLICATION TRANSMITTAL** (Large Entity)

Docket No. **CONS-0107** 

Total Pages in this Submission

(Only for new nonprovisional applications under 37 CFR 1.53(b))

#### TO THE ASSISTANT COMMISSIONER FOR PATENTS

**Box Patent Application** Washington, D.C. 20231

Transmitted herewith for filing u	inder 35 U.S.C. 111(a) a	and 37 C.F.R. 1.53(b)	) is a new utility pate	nt application for an
invention entitled:				

nventi				01 11	ing under 55	0.0.		4 37 C.F.K. 1.50	- -	o) is a new utility paterit ap	opiication for an
CO	NTAI	NER	ЕХН	1 <b>B</b> 17	ring impro	VED	TOP LOAD	PERFORMANO	CF		7242 7242
and inv	ente	d by:									28 20
Kan	ninen	i, et :	al.								1000
If a C	ONTI	NUA	TION	API	PLICATION,	chec	k appropriate	box and supply	/ tl	he requisite information:	
	onti	nuat	ion		Divisional		Continuation	on-in-part (CIP)	)	of prior application No.:	
Which	is a	:									
	onti	nuat	ion		Divisional		Continuation	on-in-part (CIP)	)	of prior application No.:	
Which	is a	:									
	onti	nuat	ion		Divisional		Continuation	on-in-part (CIP)	)	of prior application No.:	
	_										
Enclo:	sed a	ire:					Applica	tion Elements			
1.	×	Filin	n fee	26 (	ralculated and	d trar	nemitted as d	escribed below			
••		1 1111	.g icc	40 (		<i></i>	10,1111.00 00 0				
2.	$\boxtimes$	Spe	cificat	tion	having		8	pages and	in	icluding the following:	
	a.	X	Desc	cripti	ive Title of the	e Inv	ention				•
	b.		Cros	s R	eferences to	Relat	ted Application	ons (if applicable	<del>)</del> )		
	c.		State	eme	nt Regarding	Fede	erally-sponso	red Research/D	)e\	velopment (if applicable)	
	d.		Refe	ren	ce to Sequen	ce Li	sting, a Table	e, or a Compute	r F	Program Listing Appendix	
		×			und of the Inv			•			
		<u> </u>		_	mmary of the			•			
	g.	X			scription of th			d)			
					Description			<del>-</del> /			
		<u>×</u>			as Classified	l Bal	OW				
				•	of the Disclo		J44	•	•		
	j.	X	ADSI	Joen	or the Disclo	sure					

## UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. CONS-0107

Total Pages in this Submission

		Application Elements (Continued)
3.	X	Drawing(s) (when necessary as prescribed by 35 USC 113)
	a.	Number of Sheets 2 sheets bearing Figs. 1-4
	b.	☐ Informal Number of Sheets
4.	X	Oath or Declaration
	a.	☐ Newly executed (original or copy) ☑ Unexecuted
	b.	☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional application only)
	C.	☑ With Power of Attorney ☐ Without Power of Attorney
	d.	DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5.	□.	Incorporation By Reference (usable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6.		CD ROM or CD-R in duplicate, large table or Computer Program (Appendix)
<b>7</b> .		Application Data Sheet (See 37 CFR 1.76)
8.		Nucleotide and/or Amino Acid Sequence Submission (if applicable, all must be included)
	a.	☐ Computer Readable Form (CRF)
	b.	☐ Specification Sequence Listing on:
		i. CD-ROM or CD-R (2 copies); or
		ii. D Paper
	C.	Statement(s) Verifying Identical Paper and Computer Readable Copy
		Accompanying Application Parts
9.		Assignment Papers (cover sheet & document(s))
10.		37 CFR 3.73(B) Statement (when there is an assignee)
11.		English Translation Document (if applicable)
12.	X	Information Disclosure Statement/PTO-1449   Copies of IDS Citations
13.		Preliminary Amendment
14.	$\boxtimes$	Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
15.		Certified Copy of Priority Document(s) (if foreign priority is claimed)
16.	X	
		☐ First Class ☒ Express Mail (Specify Label No.): EL606862124US

# UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. CONS-0107

Total Pages in this Submission

	Accompanying Application Parts (Continued)
17.	Additional Enclosures (please identify below):
	Request That Application Not Be Published Pursuant To 35 U.S.C. 122(b)(2)
18. [	Pursuant to 35 U.S.C. 122(b)(2), Applicant hereby requests that this patent application not be published pursuant to 35 U.S.C. 122(b)(1). Applicant hereby certifies that the invention disclosed in this application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication of applications 18 months after filing of the application.
	Warning
	An applicant who makes a request not to publish, but who subsequently files in a foreign country or under a multilateral international agreement specified in 35 U.S.C. 122(b)(2)(B)(i), must notify the Director of such filing not later than 45 days after the date of the filing of such foreign or international application. A failure of the applicant to provide such notice within the prescribed period shall result in the application being regarded as abandoned, unless it is shown to the satisfaction of the Director that the delay in submitting the notice was unintentional.
	·

## UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No. CONS-0107

Total Pages in this Submission

#### **Fee Calculation and Transmittal**

#### **CLAIMS AS FILED** For #Filed #Allowed #Extra Rate Fee \$0.00 **Total Claims** -20 =0 \$18.00 14 \$0.00 1 0 \$84.00 Indep. Claims - 3 = \$0.00 Multiple Dependent Claims (check if applicable) \$750.00 **BASIC FEE** \$0.00 OTHER FEE (specify purpose) **TOTAL FILING FEE** \$750.00 A check in the amount of \$750.00 to cover the filing fee is enclosed. The Commissioner is hereby authorized to charge and credit Deposit Account No. 50-0462 as described below. A duplicate copy of this sheet is enclosed. Charge the amount of as filing fee. Credit any overpayment. ☑ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17. Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b). Signature John L. Knoble - Registration No. 32,387 Dated: March 12, 2003 KNOBLE & YOSHIDA, LLC Eight Penn Center, Suite 1350 1628 John F. Kennedy Blvd.

CC:

Philadelphia, PA 19103 Tel: (215) 599-0600

Customer No. 21,302

rostro. Graves

ERTIFICATE OF	MAILING BY "EXPRESS I	MAIL" (37 CFR 1.10)	Docket No.
oplicant(s): Kamineni			CONS-0107
Serial No.	Filing Date	Examiner	Group Art Unit
Unknown	Herewith	Unknown	Group Art Uni Unknown
			CIRRIOWII
vention: CONTAINE	R EXHIBITING IMPROVED TO	P LOAD PERFORMANCE	
I hereby certify that the	following correspondence:		· · · · · · · · · · · · · · · · · · ·
Thereby Certify that the	Tollowing Correspondence.		
Sheets of Formal Draw	ings bearing Figs. 1-4; Unexecute	ring 8 pages including claims and a d Declaration and Power of Attorn and a \$750.00 check for filing fees.	ostract of disclosure; Twey; PTO-1449 and copie
•		of correspondence)	
is haing danneited with		ce "Express Mail Post Office to A	alabananan 11 da sa
is being deposited with	The Office States Fostal Servi	ce Express Mail Fost Office to A	uaressee service una
37 CFR 1,10 in an env	elope addressed to: The Assista	int Commissioner for Patents, Wa	shington, D.C. 20231 o
March 12	. 2003		_
(Date)			
		Carla P. McDuf	
	-		fia
		(Typed or Printed Name of Person Mail	
			ing Correspondence)
		(Typed or Printed Name of Person Mail.) (Signature of Person Mailing Co.)	ing Cofrespondence)  Management of the control of t
٠		(Typed or Printed Name of Person Mail.	ing Cofrespondence)  Verespondence
		(Typed or Printed Name of Person Mail.) (Signature of Person Mailing Co. EL606862124U	ing Cofrespondence)  Verespondence
		(Typed or Printed Name of Person Mail.) (Signature of Person Mailing Co. EL606862124U	ing Cofrespondence)  Verespondence
		(Typed or Printed Name of Person Mail.) (Signature of Person Mailing Co. EL606862124U	ing Cofrespondence)  Verespondence
		(Typed or Printed Name of Person Mail.) (Signature of Person Mailing Co. EL606862124U	ing Cofrespondence)  Verespondence
	Note: Each paper must ba	(Typed or Printed Name of Person Mail.) (Signature of Person Mailing Co. EL606862124U	ing Cofrespondence)  Verespondence
	Note: Each paper must ba	(Typed or Printed Name of Person Mail.)  (Signature of Person Mailing Co.  EL606862124U  ("Express Mail" Mailing Labo	ing Cofrespondence)  Verespondence
	Note: Each paper must ha	(Typed or Printed Name of Person Mail.)  (Signature of Person Mailing Co.  EL606862124U  ("Express Mail" Mailing Labo	ing Cofrespondence)  Verespondence

## CONTAINER EXHIBITING IMPROVED TOP LOAD PERFORMANCE

#### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

5

15

20

25

This invention relates generally to the field of consumer packaging. More specifically, this invention relates to plastic containers of the type that are used to package consumer beverages, and the strength characteristics of such plastic containers.

#### 10 2. Description of the Related Technology

Plastic containers are in wide use commercially throughout the world for packaging liquids of all types, including consumer beverages. The most common type of plastic container that is used for packaging, for example, soft drinks, is fabricated from polyethylene terephthalate (PET) and is molded into a desired shape using a blowmolding process that is well known in the industry.

In the design of such containers, a number of factors are ordinarily considered. The container must be chemically resistant and should be shaped to avoid concentration of stress that result in unwanted failure. In addition, the container must be strong enough to endure the packaging process and subsequent handling during the gross packaging, shipping and retail display stages.

One type of strength that plastic containers are regularly evaluated for it is that of top load strength. Top load strength involves resistance to failure, typically sidewall buckling, when a vertical force is exerted onto the top of the container. Such vertical force is exerted onto the container during the filling process and when the closure is installed onto the container. In addition, a great deal of vertical force may be exerted onto filled containers when cases of the containers are stacked during shipping. Another type of strength that is regularly evaluated in the design of plastic containers is hoop strength. Hoop strength is the resistance provided by the

container against the tendency of the container sidewall to bow outwardly or deflect inwardly when the contents of the container are under pressurization or when external forces are applied to the outside of the container, which of course is a common scenario in the packaging and transportation of carbonated soft drinks.

It is generally known in the industry that circumferential reinforcement such as ribbing tends to increase hoop strength, and that vertical reinforcement has a favorable effect on top load strength. However, it should be understood that there is a to economic disincentive to provide any more reinforcement to a plastic container design than is absolutely necessary, because increased reinforcement tends to make the container heavier and thus more expensive to manufacture. A need exists, then, for a plastic container design that optimizes hoop strength and top load strength while minimizing the amount of plastic material that is necessary to fabricate the container.

SUMMARY OF THE INVENTION

5

10

15

20

25

Accordingly, it is an object of the invention to provide a plastic container design that optimizes hoop strength and top load strength while minimizing the amount of plastic material that is necessary to fabricate the container.

In order to achieve the above and other objects of the invention, a plastic container that is constructed according to a first aspect of the invention includes a finish portion; and a generally cylindrical main body portion, said main body portion comprising a sidewall having a first plurality of generally vertical ribs defined therein, the sidewall further having a second plurality of generally horizontal wave shaped ribs defined therein, at least one of the generally horizontal wave shaped ribs intersecting with at least one of the generally vertical ribs, whereby enhanced strength characteristics are imparted to the container.

These and various other advantages and features of novelty that characterize the invention are pointed out with particularity in the claims annexed hereto and forming a part hereof. However, for a better understanding of the invention, its advantages, and the objects obtained by

its use, reference should be made to the drawings which form a further part hereof, and to the accompanying descriptive matter, in which there is illustrated and described a preferred embodiment of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

5

10

15

20

. 25

FIGURE 1 is a side elevational view of a plastic container that is constructed according to a preferred embodiment of the invention;

FIGURE 2 is a cross-sectional view taken along lines 2-2 in FIGURE 1;
FIGURE 3 is a cross-sectional view taken along blinds 3-3 in FIGURE 1; and
FIGURE 4 is a diagrammatical depiction of one of the wave-shaped ribs with the
circumference of the container represented along the x-axis.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)**

Referring now to the drawings, wherein like reference numerals designate corresponding structure throughout the views, and referring in particular to FIGURE 1, a plastic container 10 that is constructed according to a preferred embodiment of the invention includes a finish portion 12 and a generally cylindrical main body portion 14 having an outer sidewall 16. Preferably, plastic container 10 is fabricated from a plastic material such as polyethylene terephthalate. As may be seen in FIGURE 1, body portion 14 has a first plurality of generally vertical ribs 18, 20, 22, 24 defined therein. Vertical ribs 18, 20, 22, 24, as shown in the cross-sectional view provided in FIGURE 3, are substantially concave, having a radius of depth  $R_2$ , and extend generally radially inwardly toward the center axis of the container 10. The vertical ribs are preferably parallel to each other and evenly spaced from each other over the outer circumference of the main body portion 14 of the container 10.

As may further be seen in FIGURE 1, the sidewall 16 further has a second plurality of generally horizontal wave shaped ribs 26, 28, 30, 32, 34, 36 defined therein. The generally horizontal wave shaped ribs 26, 28, 30, 32, 34, 36 preferably extend so as to be parallel with each other and are substantially evenly spaced from each other. It follows, then, that each of the wave

shaped ribs has a common amplitude A and wavelength with each of the other wave shaped ribs, with the amplitude A being defined as the peak to peak vertical distance between the uppermost point of the wave crest to the lowermost point of the adjacent wave trough and the wavelength being defined as the circumferential peak to peak distance traveled by the rib from wave crest to wave crest. Each horizontal wave shaped rib is substantially concave, having a radius of depth R<sub>1</sub>, and extending inwardly toward the center axis of the container 10. As may be seen in FIGURE 1, at least one of the generally horizontal wave shaped ribs intersects with at least one of said generally vertical ribs, whereby enhanced strength characteristics are imparted to the container.

10

15

20

25

In the preferred embodiment, it will be seen that each of the generally horizontal wave shaped ribs 26, 28, 30, 32, 34, 36 intersects with each of the 16 vertical ribs. Preferably, a plurality, and more preferably at least three of the vertical ribs intersect each wave shaped rib within each wavelength. According to one important aspect of the invention, the location or placement of the vertical ribs is harmonized with respect to the waveform of at least one of the horizontal ribs. In the preferred embodiment, the vertical ribs 18, 20, 22, 24 will intersect each of the generally horizontal wave shaped ribs 26, 28, 30, 32, 34, 36 in a repeating pattern such that each of the vertical ribs 18 intersects each wave shaped rib at the lowermost point of the wave trough, and so that each of the vertical ribs 20 intersects each wave shaped rib at a median location between the wave trough and an adjacent wave peak. Also, each vertical rib 22 will intersect each wave shaped rib at the wave peak and each vertical rib 24 will intersect each wave shaped rib at a median location between the wave peak and the next wave trough. Accordingly, at least one of the generally vertical ribs 18, 20, 22, 24 intersects at least one of the generally horizontal wave shaped ribs 26, 28, 30, 32, 34, 36 at a location of maximum amplitude of the wave shaped rib, and another one of the generally vertical ribs intersects the horizontal wave shaped rib at a location of minimum amplitude. This is believed to maximize both the hoop strength and top load strength that is achievable by the structure.

As may be visualized in FIGURE 1, sidewall 16 of the generally cylindrical main body portion 14 has an outer circumference. As is shown in FIGURE 4, which is a diagrammatical

depiction of one of the wave-shaped ribs with the circumference of the container represented along the x-axis, each wave-shaped rib preferably has a repeating wavelength  $\lambda$  and a common amplitude A. An angle  $\theta$  is defined by a triangle, two legs of which are equal to the amplitude A and one-half the wavelength  $\lambda$ . Preferably, the amplitude A of the wave shaped ribs is within a range of about 4.5 percent to about 30 percent of the wavelength  $\lambda$ , which corresponds to angle  $\theta$  being within a range of about 5 degrees to about 30 degrees. The wavelength  $\lambda$  should preferably be about 6 percent to about 40 percent of the outer circumference of the container.

5

10

It is to be understood, however, that even though numerous characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure and function of the invention, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

#### WHAT IS CLAIMED IS:

- 1. A plastic container, comprising:
  - a finish portion; and
- a generally cylindrical main body portion, said main body portion comprising a sidewall having a first plurality of generally vertical ribs defined therein, said sidewall further having a second plurality of generally horizontal wave shaped ribs defined therein, at least one of said generally horizontal wave shaped ribs intersecting with at least one of said generally vertical ribs, whereby enhanced strength characteristics are imparted to the container.
- 2. A plastic container according to claim 1, wherein said container is fabricated from a plastic material comprising polyethylene terephthalate.
- 3. A plastic container according to claim 1, wherein said first plurality of generally vertical ribs comprise at least one rib that is inwardly oriented.
- 4. A plastic container according to claim 1, wherein said second plurality of generally horizontal wave shaped ribs comprise at least one rib that is inwardly oriented.
- 5. A plastic container according to claim 1, wherein said second plurality of generally horizontal wave shaped ribs comprise a plurality of wave shaped ribs that extend generally parallel to each other.
- 6. A plastic container according to claim 1, wherein said second plurality of generally horizontal wave shaped ribs are shaped so as to have a common amplitude and a common wavelength.
- 7. A plastic container according to claim 6, wherein said common amplitude A is within a range of about 4.5 percent to about 30 percent of the common wavelength.

8. A plastic container according to claim 6, wherein said sidewall has an outer circumference, wherein said wavelength is within a range of about 6 percent to about 40 percent of said outer circumference.

- 9. A plastic container according to claim 1, wherein at least one of said generally vertical ribs intersects at least one of said generally horizontal wave shaped ribs at a location of maximum amplitude of said wave shaped rib.
- 10. A plastic container according to claim 1, wherein at least one of said generally vertical ribs intersects at least one of said generally horizontal wave shaped ribs at a location of minimum amplitude of said wave shaped rib.
- 11. A plastic container according to claim 1, wherein at least one of said generally horizontal wave shaped ribs has a periodic wavelength, and wherein a plurality of said vertical ribs intersect said wave shaped rib within each wavelength.
- 12. A plastic container according to claim 11, wherein at least three of said vertical ribs intersect said wave shaped rib within each wavelength.
- 13. A plastic container according to claim 11, wherein the location of said vertical ribs is harmonized with respect the waveform of at least one of said horizontal ribs.
- 14. A plastic container according to claim 1, wherein the location of said vertical ribs is harmonized with respect the waveform of at least one of said horizontal ribs.

#### ABSTRACT OF THE DISCLOSURE

A plastic container that exhibits an optimal ratio of hoop strength to top load strength includes a finish portion and generally cylindrical main body portion. The main body portion includes a sidewall that has a first plurality of generally vertical ribs defined therein. In addition, a second plurality of generally horizontal wave shaped ribs is defined in the sidewall. The generally horizontal wave shaped ribs intersect with the generally vertical ribs, thereby imparting enhanced strength characteristics to the container.

Docket No.	
CONS-0107	

## **Declaration and Power of Attorney For Patent Application English Language Declaration**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

#### CONTAINER EXHIBITING IMPROVED TOP LOAD PERFORMANCE

the	the specification of which						
(ch	(check one)						
	is attached hereto. was filed on Application Number		as United \$	States Application No.	or PCT International		
	and was amended on		(if ar	oplicable)			
	ereby state that I have cluding the claims, as an		erstand the c	ontents of the above ic	dentified specification,		
kn	I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.						
Se an list inv	nereby claim foreign prection 365(b) of any for y PCT International app ted below and have also ventor's certificate or PC which priority is claimed	eign application(s) dication which desi didentified below, Tinternational ap	for patent o ignated at lea by checking t	r inventor's certificate ist one country other t the box, any foreign ap	, or Section 365(a) of han the United States, oplication for patent or		
Pri	ior Foreign Application(s	5)			Priority Not Claimed		
(N:	umber)	(Country)		(Day/Month/Year Filed)			
(N	umber)	(Country)		(Day/Month/Year Filed)	0		
(N	umber)	(Country)	<del></del>	(Day/Month/Year Filed)			
TO 6	R.11 (9.95) (Modified)		P02/REV02	Ratent and Trademark C	Office-U.S. DEPARTMENT OF COM		

I hereby claim the benefit under application(s) listed below:	35 U.S.C. Section 119(e)	) of any United States provisional
(Application Serial No.)	(Filing Date)	
(Application Serial No.)	(Filing Date)	
(Application Serial No.)	(Filing Date)	
insofar as the subject matter of ea United States or PCT International U.S.C. Section 112, I acknowledge Office all information known to me	ch of the claims of this app application in the manner p the duty to disclose to the to be material to patentable between the filing date of	the United States, listed below and, plication is not disclosed in the prior provided by the first paragraph of 35 United States Patent and Trademark ility as defined in Title 37, C. F. R., the prior application and the national
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
(Application Serial No.)	· (Filing Date)	(Status) (patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Page 3 of 3

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

John L. Knoble - Registration No. 32,387 Ken I. Yoshida - Registration No. 37,009 Kevin J. Dunleavy - Registration No. 32,024 Maria M. Kourtakis - Registration No. 41,126 Donna R. Maddox - Registration No. 34,913

Send Correspondence to: KNOBLE & YOSHIDA, LLC Eight Penn Center, Suite 1350

1628 John F. Kennedy Blvd. Philadelphia, PA 19103

Direct Telephone Calls to: (name and telephone number)

John L. Knoble - 215-599-0600

Full name of sole or first inventor Satya Kamineni	
Sole or first inventor's signature	Date
Residence 816 South Adams Street, #C504, Westmont, IL 60559	
Citizenship India	
Post Office Address Same as above.	

Michael Mooney	
Second inventor's signature	Date
Residence 21356 Bramble Drive, Frankfort, IL 60423	
Citizenship US	
Post Office Address Same as above.	




FIG. 1




FIG. 4

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
Потигр

## IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.